



Aerial closure OSS-ZSD-24/8

Aerial closures OSS-ZSD-24/8, OSS-ZSD-24/12, OSS-ZSD-24/16

Features:

- designed for splicing customer drop cable fibres to the fibres of a distribution cable, dedicated for outdoor and indoor use
- the cover and base are made of high quality UV stabilised pastic with wide operating temperature range -40°C to +85°C
- hinged cover locked to the base with snap buckles and safety cylinder lock, 2 keys included
- hinged splice tray allows convenient fibre management, splitter and connectros installation
- divisible cable entry for the distribution cable loop through applications
- quick and easy installation on OSS-SZD-60 or OSS-SZD-80 cabel reserve frames with the use of the mounting plate

Equipment:

- splice protectors
- 2 lock keys
- cable ties
- fibre protection tubes
- installation kit

Optional equipment:

- OSS-SZD cable reserve frame
- mounting plate for OSS-SZD cable reserve frame

Technical specifications:

	OSS-ZSD-24/8SC/2/12-A	OSS-ZSD-24/12SC/2/12-A	OSS-ZSD-24/16SC/2/16-A
application	indoor, outdoor, aerial		
number of distribution cable entry	2		
number of customer drop cable ports	12		16
distribution cable diameter range [mm]	5 to 11		
customer drop cable diameter range [mm]	3 to 6		
maximum splice capacity	24		
number of adapter slots	8 adapters SC or LC Duplex	12 adapters SC or LC Duplex	16 adapters SC or LC Duplex
number of splitters in mini type housings	1 splitter PLC 1x8		1 splitter PLC 1x16 or 2 splitters PLC 1x8
dimensions length/width/height [mm]	260/210/90		310/240/105
cable to port sealing method	rubber seals		
sheath material	PC+ABS		
protection grade	IP65		