



Cable reserve box SZ-8

## Cable reserve box SZ-8

### Features:

- dedicated for use in cable chambers
- access to the interior protected by a key locked lid
- 6 round pre-punched cable entries, 2 open cable entry slots allowing insertion of the cable loop
- possibility of installation of up to three KS-3E splice trays
- possibility of installation of two Fibre Optic Distribution Boxes PSW-12/DIN
- standard kit outdoor cable termination plates
- space dedicated for storage and arrangement of outdoor cable loose tubes guided to splice trays and distribution boxes
- made of steel sheet finished with powder varnish

### Equipment:

- cable reserve box
- rubber bushing
- rubber gland
- DIN rail
- cable ties and bands
- lock
- KS-3E splice trays

### Optional equipment:

- fibre optic distribution box PSW-12/DIN
- splittable corrugated protective tube

### Technical specifications:

		SZ-8
fixing		4x ø6 mm 560x560 mm
number of inputs/outputs of a cable		6 round pre-punched, 2 open slots
dimensions width/height/depth [mm]		660/660/158
weight [kg]		13,8
cable capacity [m]	cable ø10 mm	100
	cable ø11 mm	100
	cable ø12 mm	80
	cable ø13 mm	60
	cable ø14 mm	50
	cable ø16 mm	30
	cable ø18 mm	20
interior access protection		lock
housing material/color		steel sheet/RAL 7035

### Ordering:

SZ-8 - cable reserve box