



Cable reserve frame SZ-4, SZ-4.2

Cable reserve boxes SZ-4, SZ-4.1, SZ-4.2

Features:

- designated for installation in cable chambers
- interior access is protected with a lid, in SZ-4.2 lockable
 capacity from 20 up to 50 m of cable, for diameters 13 and 10 mm
- guarantees functionality and proper bending radius of a cable
- forces the cable arrangement

Equipment:

- cable reserve boxmounting kitlock

Technical specifications:

		SZ-4	SZ-4.1	SZ-4.2
dimensions width/height/depth [mm]		550/550/100	450/450/130	750/750/150
weight [kg]		6,5	6	12
mounting on a wall		4 holes ø8,5 mm screw spacing 300 x 300 mm	4 holes ø8,5 mm screw spacing 250 x 250 mm	4 holes ø8,5 mm screw spacing 500 x 500 mm
number of inputs/outputs of a cable		4	4	6
cable capacity [m]	cable ø10 mm	100	50	300
	cable ø11 mm	60	-	250
	cable ø12 mm	40	-	220
	cable ø13 mm	30	-	180
	cable ø14 mm	30	-	140
	cable ø16 mm	20	-	60
	cable ø18 mm	20	-	20
interior access protection		lock		
housing material/color		steel*/RAL 7035		

^{*} Made of aluminum: SZ-4AL, SZ-4.1AL, SZ-4.2AL (option).

Ordering:

SZ-4 - spare length cable box