



Cable reserve frame SZ-4, SZ-4.2

# Cable reserve boxes SZ-4, SZ-4.1, SZ-4.2

### Features:

- designed to be installed in the outdoor cable chambers
- interior access is protected with a lid, in SZ-4.2 lockable
- capacity from 20 up to 50 m of cable, for diameters 13 and 10 mm
- guarantees functionality and proper bending radius of a cable

### Equipment:

- positive cable arrangement
- cable reserve box
- mounting kit
- lock

### Technical specifications:

|                                     |              | SZ-4  | SZ-4.1  | SZ-4.2  |
|-------------------------------------|--------------|---|---|---|
| dimensions width/height/depth [mm]  |              | 550/550/100                                   | 450/450/130                                   | 750/750/150                                   |
| weight [kg]                         |              | 6,5   | 6   | 12  |
| mounting on a wall                  |              | 4 holes ø8,5 mm screw<br>spacing 300 x 300 mm | 4 holes ø8,5 mm screw<br>spacing 250 x 250 mm | 4 holes ø8,5 mm screw<br>spacing 500 x 500 mm |
| number of inputs/outputs of a cable |              | 4   | 4   | 6   |
| cable capacity [m]                  | cable ø10 mm | 100   | 50  | 300   |
|                                     | cable ø11 mm | 60  | -   | 250   |
|                                     | cable ø12 mm | 40  | -   | 220   |
|                                     | cable ø13 mm | 30  | -   | 180   |
|                                     | cable ø14 mm | 30  | -   | 140   |
|                                     | cable ø16 mm | 20  | -   | 60  |
|                                     | cable ø18 mm | 20  | -   | 20  |
| interior access protection          |              | lock  |   |   |
| housing material/color              |              | steel*/RAL 7035                               |   |   |

\* Made of aluminum: SZ-4AL, SZ-4.1AL, SZ-4.2AL (option).

### Ordering:

SZ-4 - spare length cable box