

Cable reserve frame SZ-7/N

Features:

- dedicated for use in cable chambers
- hinged frames for the storage of spare cable coils
- easy access to all cables routed from the top or from the bottom
- capacity of one hinged frame: 4 cable coils, 60 up to 150 m each
- maximum coil diameter: 800 mm
- installation of 4 additional SZ-7K spare cable frames on each hinged frame possible
- SZ-7K is used for smaller diameter cables with the maximum coil diameter of 550 mm
- maximum capacity of SZ-7K frame: 50 m of the cable with 10 mm diameter
- maximum capacity of SZ-7/4 with 4 frames is 32 cable coils (only if 4 SZ-7k frames are used)
- made of steel profiles finished with powder varnish in RAL 7035 colour

Equipment:

- cable reserve frame
- installation kit
- cable ties

Optional equipment:

- additional cable reserve frame SZ-7K

Technical specifications:

	SZ-7/1	SZ-7/2	SZ-7/3	SZ-7/4	SZ-7/3/M
number of hinged frames	1	2	3	4	-
fixing	standing				
dimensions width/height/depth [mm]	350/1700/850	600/1700/850	850/1700/850	1100/1700/850	1000/1750/400
weight [kg]	35	50	65	80	65
maximum number of cable coils*	4	8	12	16	-
cable capacity [m]	cable ø10 mm	4 x po 150 m	2 x (4 x po 150 m)	3 x (4 x po 150 m)	4 x (4 x po 150 m)
	cable ø11 mm	4 x po 120 m	2 x (4 x po 120 m)	3 x (4 x po 120 m)	4 x (4 x po 120 m)
	cable ø12 mm	4 x po 100 m	2 x (4 x po 100 m)	3 x (4 x po 100 m)	4 x (4 x po 100 m)
	cable ø13 mm	4 x po 90 m	2 x (4 x po 90 m)	3 x (4 x po 90 m)	4 x (4 x po 90 m)
	cable ø14 mm	4 x po 75 m	2 x (4 x po 75 m)	3 x (4 x po 75 m)	4 x (4 x po 75 m)
	cable ø16 mm	4 x po 50 m	2 x (4 x po 50 m)	3 x (4 x po 50 m)	4 x (4 x po 50 m)
	cable ø18 mm	4 x po 20 m	2 x (4 x po 20 m)	3 x (4 x po 20 m)	4 x (4 x po 20 m)
housing material/color	steel/RAL 7035				

* For cables with 10mm diameter there is a possibility of doubling the number of cable coils by the application of SZ-7K frames.

NOTICE:

1. Frame heights: 1.7 m without the base, 2.0 m with the base.
2. SZ-7K frames and lateral plates to be ordered separately.

SZ-7/3M:

- stores up to 15 optical cable splice closures
- stores optical splice closures of diameter up to 300 mm

Ordering:

SZ-7/2 - cable reserve frame with two hinged frames for 8 outdoor cable coils



SZ-7/2



Additional cable reserve frame SZ-7K



SZ-7/3/M