



Fibre optic distribution box PS-3/144

Fibre optic distribution box PS-3

Features:

- wall mounted in controlled environments
- termination of up to 72 fibres, 6 cable entries
- storage space for patchcord cable under adapter plate
- full front access to splice trays and adapter plate
- hinged splice trays allowing convenient maintenance

The set includes:

- splice trays KS-3E, cable organisers
- cable ties, cable rubber glands
- installation and handling instructions
- installation kit

Technical specifications:

	PS-3/24	PS-3/48	PS-3/72	PS-3/144
number of splice trays	1 x KS-24	2 x KS-24	3 x KS-24	6 x KS-24
maximum number of splices	24	48	72	144
adapter capacity	144			
connector standard	E-2000, SC, FC, ST, LC			
recommended pigtail length [m], 0,9 mm buffered fibre	2,5			
recommended pigtail length [m], 2 mm cable diameter	1,5			
number of outdoor cable entries	6			
maximum diameter of input cable [mm]	14			
dimensions: width/height/depth [mm]	365/410/185			
weight [kg]	7			
housing material/colour	steel sheet/RAL 7035			
mechanical protection IK	IK 08			
environmental protection IP	IP31			

Ordering:

PS-3/72/K/72E2A - wall mounted fibre optic distribution box equipped with 72 pigtails and 72 E2000/APC adapters