



LGX compatible MPPO modules

Housing (LGX) ^{MPPO}

Features:

- compliant with LGX standard
- mechanical protection for passive optical devices
- optical passive device terminals available on the module front plate, adapter standard upon request
- fixed in 1U, 2U, 3U PPO-1 frames to be installed in 19" racks or 19" cabinets
- fixed in PPO-48, PPO-72 frames to be installed in PSU-1 cabinets
- MPPO-1-MS, MPPO-1-MS-Z modules with connectorised cable leads on the panel front

Technical specifications:

MPPO housing				
	MPPO-1	MPPO-2	MPPO-3	MPPO-4
adapter capacity	10	18	34	66
dimensions width/height/depth [mm]	30/130/158	60/130/158	90/130/158	180/130/158
MPPO capacities, E-2000/SC terminations				
optical circulators CR-3	2 pcs	6 pcs	11 pc	22 pcs
optical circulators CR-4	1 pc	3 pcs	6 pcs	12 pcs
optical circulators CR-8	1 pc	3 pcs	6 pcs	12 pcs
WDM multiplexers	3 pcs	6 pcs	11 pc	22 pcs
CWDM/DWDM multiplexers/demultiplexers	one 8 channel MUX/DEMUX	one 8/16 channel MUX/DEMUX	one 16 channel MUX/DEMUX	-
FBT Couplers	3 pcs	6 pcs	11 pc	22 pcs
PLC Splitters	3 pcs 1x2 2 pcs 1x4 1 pc 1x8	1 pc 1x16	1 pc 1x32	1 pc 1x64

Ordering:

MPPO-1 - LGX compatible module for passive optical components