



Modular patch panel PSM-19/144/3U

Modular patch panel PSM-19/144/3U

Features:

- capacity up to 12 modules MPS-19/12/W
- quick and reliable fibre links configuration
- easy access for performing control and maintenance measurements
- storage and organisation of outdoor cable loose tubes requires application of 19" Excess cable tray SZ-19L-1U
- blank plates PZ-3U-7 (width 35 mm) to cover unused space in the panel
- installation in 19" racks with minimum depth of 300 mm, e.g. STP-19
- installation in 21" and/or 23" racks with the use of AD-19 adapters

The set includes:

- cable ties and cable bands
- installation and handling instructions
- installation kit
- 19" Excess cable tray SZ-19L-1U (optional)
- blank plate (optional)

Technical specifications:

	PSM-19/144/3U
number of splice trays	max. 12 x KSQ
maximum number of splices	12 per module
adapter capacity	12 modules x 12 pcs = 144
connector standard	E-2000, SC
recommended pigtail length [m], 0,9 mm buffered fibre	1 - 1,5
dimensions: width/height/depth [mm]	483/132 (3U)/210
weight [kg]	4
number of modules	12
module type	MPS-19/12/W
mounting brackets position	front

Ordering:

PSM-19/144/3U - modular patch panel, height 3U