



Modular patch panel PSM-19/144/4U

# Modular patch panel PSM-19/144/4U

## Features:

- capacity up to 12xMPK-12 modules
- quick and reliable fibre links configuration
- easy access for performing control and maintenance measurements
- height 4U, includes integrated 1U patchcord cable or outdoor cable loose tube excess lengths tray
- outdoor cable loose tubes organiser allows fixation of guiding protective tubes routed to the installed modules
- outdoor cables and patchcords can be routed into the panel from the left or right side
- installation in 19" racks with minimum depth of 300 mm, e.g. STP-19
- installation in 21" and/or 23" racks with the use of AD-19 adapters

## The set includes:

- outdoor cable loose tubes and patchcord excess lengths tray
- universal adapter for front or rear fixing in 19" racks
- ingoing outdoor cable loose tubes organiser, outgoing pigtails organiser
- cable ties and cable bands
- installation and handling instructions
- installation kit

## Technical specifications:

	PSM-19/144/4U
number of splice trays	max. 12 x KSQ
maximum number of splices	144
adapter capacity	144
connector standard	E-2000, SC
LC Duplex adapter capacity	96 - 144
recommended pigtail length [m], 0,9 mm buffered fibre	1,5
number of outdoor cable entries	12
dimensions: width/height/depth [mm]	488/175/290
weight [kg]	3,7
number of modules	12
module type	MPK-12
mounting brackets position	rear/front

## Ordering:

PSM-19/144/4U - modular patch panel, height 4U