



Module MPS-19/12/W

Module MPS-19/12/W

Features:

- dedicated for PSM-19/144/3U
- termination of up to 12 fibres

The set includes:

- module frame
- adapter plate
- KSQ splice tray
- pigtail excess cable length basketinstallation and handling instructions

Technical specifications:

	MPS-19/12/W
adapter capacity	12
connector standard	E-2000, SC
recommended pigtail length [m], 0,9 mm buffered fibre	1 - 1,5
adapter plate width [mm]	35
dimensions: width/height/depth [mm]	35/132 (3U)/195

Front panel for 12 x LC adapters can be made on request.

Ordering:

MPS-19/12/W/E/SC - module for 12 pigtails and 12 adapters E2000 or SC dedicated for modular patch panels PSM-19/144/3U

MPS-19/12W/K/12E2A - complete module equipped with 12 pigtails and 12 adapters E2000/APC dedicated for modular patch panels PSM-19/144/3U

This document is intended as a guide only. Whilst the information it contains is believed to be correct, OPTOMER can take no responsibility for actions taken based on the information contained in this document OPTOMER reserves the right to make changes to this document without notice. All sales of product are subject to OPTOMER's terms and conditions of sale only, which can be found on OPTOMER's website. This document is protected by copyright 60 OPTOMER Meller Restelskip j. [202]. The product sale yield are protected by constructions can be found on OPTOMER's website. This is prohibited and OPTOMER will take action to prevent any infringement of its rights and to claim damages for the loss that it suffers.