



6 fibre pigtail fan out, PSKD cable



24 fibre pigtail fan out, MINI BREAKOUT cable



24 fibre patchcord fan out BREAKOUT cable

# Multipigtails, multipatchcords

## Features:

- cable bundles, can be terminated by E-2000, SC, LC, FC or ST connectors
- eliminate the need for splicing or mechanical connecting fibres in the field
- reduction of costs
- cable bundle can be protected by tubes or splittable corrugated tubes
- different configurations of endings - e.g. cascade
- available cable bundles:
  - breakout with 2.0 mm cables for indoor use
  - mini-breakout with 0.9 mm buffered fibres for indoor use
  - universal cable for outdoor use
  - PSKD tactical cable with 0.9 mm buffered fibres for outdoor applications

## Configurations:

fan out cable WK	connector on side A	connector on side B	fibre count	cable length L [m]	fibre type	cable type
Defined by the customer	E28 E-2000/APC DIAMOND	E28 E-2000/APC DIAMOND	SM MM 4J 4G 6J 6G 8J 8G 12J 12G 24J 24G 48J 48G		INDOOR	
	E20 E-2000/PC DIAMOND	E20 E-2000/PC DIAMOND			SM G.652D (SM1) MMG.651 62,5 (OM1) MMG.651 50 (OM2)	A - mini Breakout with 0.9 mm buffered fibres
	E28R E-2000/APC 0,1 dB DIAMOND	E28R E-2000/APC 0,1 dB DIAMOND			SMG.652D (SM1) MMG.651 62,5 (OM1) MMG.651 50 (OM2)	B - breakout with 2 mm cables
	SCA SC/APC	SCA SC/APC	SM MM 4J 4G 6J 6G 12J 12G		SMG.652D (SM1) SMG.657 A1 SMG.657 A2 MMG.651 62,5 (OM1) MMG.651 50 (OM2) MMG.651 50 (OM3) MMG.651 50 (OM4)	C - patchcord cable bundle in protective corrugated tube with the bushing
	SCP SC/PC	SCP SC/PC			Universal indoor/outdoor	
	SC SC MM	SC SC MM	SM MM 4J 4G 6J 6G 8J 8G 12J 12G 24J 24G 48J 48G		SMG.652D (SM1) MMG.651 62,5 (OM1) MMG.651 50 (OM2)	D - with 2 mm cables
	LCP LC/PC	LCP LC/PC			SMG.652D (SM1) MMG.651 62,5 (OM1) MMG.651 50 (OM2)	E - with 2 mm cables and fibre manifold
	LCA LC/APC	LCA LC/APC			SM G.652D (SM1) MMG.651 62,5 (OM1) MMG.651 50 (OM2)	F - with 0.9 mm buffered fibres
		X - no connector	SM MM 4J 4G 6J 6G 12J 12G		TACTICAL	
					SMG.652D (SM1) MMG.651 62,5 (OM1) MMG.651 50 (OM2)	M - PSKD with 0.9 mm buffered fibres

Notice: lengths of the shortest leads dA, dB and the sA, sB length increments should be specified in addition to the code.

## Ordering:

WK/E2A/E2A/24J/25/SMG.652D/B - patchcord fan out, E-2000/APC connectors on both ends, 24 fibres, length 25 m, SM G.652D fibre, BREAKOUT cable