

## PRW-32U, PRW-64U WALL-MOUNTED ACCESS NETWORK DISTRIBUTION SPLICE BOX

### FEATURES:

- wall-mounted access network distribution splice box dedicated to connect fibres of feeder cables with subscriber cable fibres
- used as a fibre distribution box in multi-dwelling units
- capacity up to 64 subscriber connections (PRW-64U)
- 2 prepunched cable entries on each side wall
- each cable entry for up to 3 cables
- hinged splice trays each accommodating 24 splices
- adapter plate to connect inputs of four splitters
- dedicated splice tray to connect feeder cable fibres
- powder paint finished steel box
- stores up to 7 splice trays (PRW-64U)

### EQUIPMENT:

- lockable housing
- splice trays
- ø37 mm duct entry plugs
- cable ties, small
- cable ties, large

### TECHNICAL SPECIFICATIONS:

	PRW-32U	PRW-64U
dimensions height/width/depth [mm]	305/251/105	375/381/125
number of splitters (minihousing)	max. 4	
maximum number of splices	72	168
recommended number of connections - subscriber side	32	64
recommended number of connections – feeder side	4	
number of cable entries	8	9
maximum diameter of the entering cable [mm]	ø37	
housing material/colour	powder paint finished steel box / RAL 7035	
environmental IP protection	IP41	

- protective tape
- TPI table for descriptions
- mounting kit

### ADDITIONAL ACCESSORIES:

- OZRWL - cable marker roll dispenser (self-adhesive)
- SZKLD - easy access cable coiling box



*PRW-32U Wall-Mounted Access Network Distribution Splice Box*



*PRW-64U Wall-Mounted Access Network Distribution Splice Box*