

## PSM COMPACT FIBRE OPTIC DISTRIBUTION BOX

## FEATURES:

- wall or 35 mm DIN rail mounted
- easy installation in telecom and power cabinets
- termination of up to 4 fibres, 2 cable entries
- organisation of fibre routing tubes vertical and horizontal
- splice box option for branch cables - additional splice
- protector holder required

## THE SET INCLUDES:

- fibre organiser
- splice protector holder, cable ties
- installation and handling instructions
- installation kit
- DIN rail fitting (ordered separately)

## TECHNICAL

	PSM-1/4	PSM-2/4
number of splice trays		-*
maximum number of splices	4/max. 8	6
adapter capacity		4
connector standard	E-2000, SC	
recommended pigtail length [m], 0.9 mm buffered fibre	0,5	
recommended pigtail length [m], 2 mm cable diameter	-	
number of outdoor cable entries	4	2
maximum diameter of input cable [mm]	10	14
dimensions: width/height/depth [mm]	90/145/20	90/195/35
weight [kg]	0,5	
housing material/colour	steel sheet/RAL 7035	
mechanical protection IK	IK 08	
environmental protection IP	IP20	

\* splice protector holder

## ORDERING:

PSM-DIN-4/K/4E2A - wall mounted Compact Fibre Optic Distribution Box, equipped with 4 pigtails and 4 E2000/APC



Compact Fibre Optic Distribution Box  
PSM-1/4



Compact Fibre Optic Distribution Box  
PSM-2/4