

## PSW-12/DIN FIBRE OPTIC DISTRIBUTION BOX



*Fibre Optic Distribution Box  
PSW-12/DIN*

### FEATURES:

- wall or 35 mm DIN rail mounted
- easy installation in telecom and power cabinets
- termination of up to 12 fibres, 2 cable entries
- back or side mounting
- captive screw mounted lid

- cable strength member clamps
- installation and handling instructions
- installation kit (for DIN rail)

### THE SET INCLUDES:

- KS-Q splice tray
- cable ties, spiral protection sleeve

### TECHNICAL SPECIFICATIONS:

|   | PSW-12/DIN             |
|---|------------------------|
| number of splice trays                                | 1 x KSQ                |
| maximum number of splices                             | 12                     |
| adapter capacity                                      | 12                     |
| connector standard                                    | E-2000, SC, FC, ST, LC |
| recommended pigtail length [m], 0.9 mm buffered fibre | 1,5                    |
| recommended pigtail length [m], 2 mm cable diameter   | -                      |
| number of outdoor cable entries                       | 2                      |
| maximum diameter of input cable [mm]                  | 12,8                   |
| dimensions: width/height/depth [mm]                   | 40/220/120             |
| weight [kg]   | 1,2                    |
| housing material/colour                               | steel sheet/RAL 7035   |
| mechanical protection IK                              | IK 08                  |
| environmental protection IP                           | IP20                   |

### ORDERING:

PSW-DIN-12/K/12E2A - wall mounted Fibre Optic Distribution Box equipped with 12 pigtails and 12 E2000/APC

TELECOM

ACCESS

CATV

MAN

WAN

LAN

FTTx

PON

xWDM

