



Wall-mounted floor box NSP-1

Features:

- · dedicated to make customer drop connections in multilevel units
- mountable on existing riser cable
- dedicated to ø37 mm ducts
- up to 12 splices
- 2 customer drop cable entries on side walls
- lockable

Equipment:

- cable glands
- cable ties and tapes
- protective tape
- mounting kit
- TPI table for descriptions

Technical specifications:

	NSP-1
dimensions: height/width/depth [mm]	206/177/60
number of KS-12 splice trays	1
maximum length of a single 0.9 mm buffered fibre storaged in the box [m]	5
number of holes for rubber glands top/bottom	1/1
number of holes for rubber glands left/right	2/2
housing/equipment material	steel/ABS

Wall-mounted floor box NSP-1

This document is intended as a guide only. Whilst the information it contains is believed to be correct, OPTOMER can take no responsibility for actions taken based on the information contained in this document. OPTOMER reserves the right to make changes to this document without notice. All sales of product are subject to OPTOMER's terms and conditions of sale only, which can be found on OPTOMER's website. This document is protected by copyright © OPTOMER Meller Restelskis [1, [202]. The products depicted are protected by conserving of this document or of our products is prohibited and OPTOMER will take action to prevent any infringement of its rights and to claim damages for the loss that it suffers.