



Loose organised thin-wall microduct

# Loose organised thin-wall microduct bundles

## Features:

- designed for direct bury or duct installation
- microducts count and diameter is selected according to customer's needs
- build of thin-walled microducts with low friction factor
- high pressure resistance
- protective tube in orange or black
- available in different colours or transparent form with colored bar (for special order)

## Technical specifications:

quantity / type of microtube	7x7/5	8x7/5	4x10/8	7x10/8	4x12/10	7x12/10
material	poliethylen HDPE					
external package dimensions [mm]	21,5	25,6	28,8	34,6	33,6	40,6
internal package dimensions [mm]	16,9	21	24,2	30	29	36
number of microducts in the package	4	7	4	7	4	7
microtubes dimensions [mm]	7/5		10/8		12/10	
maximum pulling strength [N]	5700	6450	7850	10300	9400	15700
temperature range for transport, work and storing [°C]	-40 to +70					
installation temperature [°C]	-10 to +50					
prefabricated length [mb]	2000					
weight [kg/km]	203	369	365	566	509	774

## Ordering:

MIK	DBL (loose organization)	count and diameter of microtubes [mm]	microtube with pull cord
		7x7/5	
		8x7/5	
		4x10/8	
		7x10/8	
		4x12/10	
		7x12/10	
MIK	DBL	4x10/8	+P