



DC-LGX-8LCDX/2MPO-1XKSQ Module

DC-LGX-8LCDX/2MPO-1XKSQ Module

Features:

- LGX compatible
- Installation and breakout of fibre optic cable
- Space for the slack lengths of cable and fibre loose tubes
- Provides maximum space savings in IT cabinets and reduces installation time
- 24 fusion splices
- The module allows:
 - Splicing of 24 optical fibres
 - Installation of 2 MPO adapters
 - Installation of 8 LC DX adapters
 - Storage of slack patchcord cables in a dedicated patchcord storage tray
 - Installation of OFBLT protective tubes and WO-10 corrugated tube in cable entries
 - Installation in DC-LGX-PPO-1 frames

Accessories:

- KSQ splice tray
- Cable management brackets
- 2 x fixing latch for DC-LGX-PPO-1 frame

Additional accessories:

- MPO adapter
- LC adapter
- Adapter fixing screws

Technical Specifications:

	DC-LGX-8LCDX/2MPO-1XKSQ Module
Dimensions [mm]: Width x Height x Depth	128x28x355
Material, coating	aluminium, powder coating
Maximum number of MPO connectors	2
Maximum number of LC connectors	16
Adapter standard on front panel	LC DX, MPO
Maximum length of a single slack fibre [m]	2.5
Maximum diameter of input cable [mm]	11.5